

Technical drawing of a square plate with a central octagonal hole and four diagonal slots. The drawing includes dimensions: a horizontal distance of $.743 \pm .020$ from the center to the edge, a vertical distance of $1.485 \pm .020$ SQ from the center to the edge, and a reference dimension of $.50$ REF TYP. A section line A-A is indicated by a dashed line and arrows.

E
EXTENDED LINER
(ORIENTATION IS INDEPENDENT
OF THE SCREW HOLES)

OPEN
.40W X .10H
REF

SEE NOTE 2

.245±.020

T

Notes

1. TAPE MAY BE FLUSH OR EXTEND BEYOND THE EDGE OF THE MOUNT
2. TAPE MAY BE FLUSH OR INSIDE THE MOUNT EDGE
3. MOUNTING SURFACE, APPLYING ADHESIVE TO, IS CLEAN, DRY, AND FREE OF GREASE AND OIL. IT IS RECOMMENDED TO USE 50:50 MIXTURE OF IPA (ISOPROPYL ALCOHOL) AND WATER PRIOR TO APPLYING
4. STORE PRODUCT IN ITS ORIGINAL PACKAGING BETWEEN 50°F TO 86°F (10°C TO 30°C) AND 50% OF RELATIVE HUMIDITY, OUT OF DIRECT SUNLIGHT
5. STORE PRODUCT IN ITS ORIGINAL PACKAGING BETWEEN 40°F TO 100°F (4°C TO 38°C) AND 0-95% RELATIVE HUMIDITY, THE OPTIMUM STORAGE CONDITIONS ARE 72°F (22°C) AND 50% RELATIVE HUMIDITY OUT OF DIRECT SUNLIGHT.

SEE CHART SHEET 2

The copyright of this drawing is reserved by HellermannTyton. It is issued on condition that it is not reproduced, copied, or disclosed to a third party, either wholly or in part, without the consent of HellermannTyton.

Drawn	KEP	4/13/2016
Approved	KAC	4/13/2016

HellermannTyton
 North America
 Email: corp@ntamericas.com
 Web: www.hellermann.tyton.com

Article/Type-No	SEE CHART SHEET 2
Title	MOUNTING BASE, 4 WAY, MB5, SELF-ADHESIVE
Drawing-No	PRODUCTION : Ph 16-0340-001-CSU

Scale	2:1
Project Number	PRP16-0340
Format	B
Sheet	1/2

SW	Revision level			Revision Record	Changed	Date	Approved	Date
	Drawing	State	Part					
	07.2	Design Release	-	SEE ECN# 311315	CAS	07/10/2024	KAJ	07/10/2024

SCALE 1:1

07.2

TYPE NAME	E ±0.030	T ±0.005	STORAGE CONDITIONS	MOUNTING METHOD	MOUNT MATERIAL	COLOR	CABLE TIE SERIES
MB5	N/A	N/A	N/A	#8 SCREW (NOT INCLUDED)	PA66	BLACK	T18 THRU T150
						WHITE	
					PA66HIRHSUV	BLACK	
MB5A	0.036	0.134	SEE NOTE 5	241-001-03 RUBBER FOAM TAPE (RECOMMENDED FOR INDOOR USE ONLY)	PA66	BLACK	
						WHITE	
					PA66HIRHSUV	BLACK	
	0.045	0.130	SEE NOTE 6	24-1094-01 ACRYLIC FOAM TAPE	PA66	BLACK	
						WHITE	
	0.045	0.130	SEE NOTE 6	URAD5PX5011E ACRYLIC FOAM TAPE	PA66HIRHSUV	BLACK	

Notes
SEE SHEET 1

Material

SEE CHART SHEET 2

Units: inches

Dimension without tolerances details to:
.xxxx = ±.0005
.xxx = ±.005
.xx = ±.01
.x = ±.03
None = ±.06
∠ = ±0.5°
Dimension Formatted in/[mm]

The copyright of this drawing is reserved by HellermannTyton. It is issued on condition that it is not reproduced, copied, or disclosed to a third party, either wholly or in part, without the consent of HellermannTyton.

Drawn

KEP

4/13/2016

Approved

KAC

4/13/2016

HellermannTyton
North America
Email: corp@htamericas.com
Web: www.hellermann.tyton.com

Article/Type-No
SEE CHART SHEET 2

Title
MOUNTING BASE, 4 WAY, MB5, SELF-ADHESIVE

Drawing-No
16-0340-001-CSU

PRODUCTION : Phase

Scale
2:1

Project Number
PRP16-0340

Format
B

Sheet
2/2