

UL 1015 Hook-Up Wire - Type WRT

Waytek Stock No.	Gauge	Colors Available	Standard Put-up Ft.	Approx. Weight Lbs./mft.	Stranding	Nom. OD In. (mm)	Wall Thk Mils (mm)
WRT22	22	0 thru 9	250, 500, 1000, 2500, 7500	5.5	7/30	0.090 (2.29)	30 (0.76)
WRT20	20	0 thru 9	250, 500, 1000, 2500, 5000	6.8	10/30	0.098 (2.49)	30 (0.76)
WRT18	18	0 thru 9	250, 500, 1000, 2500, 5000	10	16/30	0.056 (2.74)	30 (0.76)



Features:

- Tinned Copper
- Tinned copper is more resistant to corrosion and easier to solder compared to bare copper
- UL re-spooled capabilities are available upon request
- Meets flammability rating VWI
- UL1015/1230/MTW 221°F (105°C) 600V
- UL1032 194°F (90°C) 1000V
- CSA TEW 221°F (105°C) 600V

COLORS		
0- Black	1 - Brown	2 - Red
3 - Orange	4 - Yellow	5 - Green
6 - Blue	7 - Violet	8 - Gray
9 - White		

UL Print Legend:

WRT20: E132579 **20** AWG (UL) MTW OR AWM STYLES 1015 OR 1230 105C 600V OR STYLE 1032 90C 1000V VW-1 CSA LL37082 TEW 105C 600V FT-1 AWM I A/B

WRT18: E1132579 **18** AWM (UL) MTW OR AWM STYLES 1015 OR 1230 105C 600V OR STYLE 1032 90C 1000V VW-1 CSA LL37082 TEW 105C 600V FT-1

UNCONTROLLED DOCUMENT
 All information provided by manufacturer
 Subject to change
 Updated 5/26/2011