

HDM190HIRH4



Article Number: 151-00436

Standard Torque Mount, Mounting Hole .1875", Max Torque 115.0 lbs, PA66HIRHSUV, Black, 500/pkg



Download spec sheet

Base Data

Local Order Number	HDM190HIRH4
Type	HDM19
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none">• Mount and tie combination makes it easy to service bundles in the field.• Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.• Eliminates the needs for multiple sized fix diameter clamps.
Product Description	HellermannTyton mounts when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps, which reduces inventory and purchasing costs while simplifying the assembly process.
Fixation Method (FF)	Screw Mounting and Rivet
Short Description	Standard Torque Mount, Mounting Hole .1875", Max Torque 115.0 lbs, PA66HIRHSUV, Black, 500/pkg

Product Dimensions

Length L (imperial)	1.4 "
Length L (metric)	36.3 mm
Width W (imperial)	0.8 "
Width W (metric)	19.3 mm
Cable Tie Width Max (imperial)	0.5 "
Cable Tie Width max. (metric)	12.7 mm
Width W2 (imperial)	0.5 "
Width W2 (metric)	13.3 mm
Height H (imperial)	0.7 "
Height H (metric)	16.7 mm
Height H2 (imperial)	0.3 "
Height H2 (metric)	8.0 mm
Mounting Hole Diameter D (imperial)	0.2 "
Mounting Hole Diameter D (metric)	4.7 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	500
Carton Quantity	4000

Material and Specifications

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut	PA66HIRHSUV
Flammability	UL94 HB
Maximum Torque (kgf-cm)	132.5 kgf-cm
Maximum Torque (lbf-ft)	9.583 lbf-ft
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Conformity	Yes