

UL 1061 Hook-Up Wire - Type WST

Waytek Stock No.	Gauge	Colors Available	Standard Put-up Ft.	Approx. Weight Lbs./mft.	Stranding	Nom. OD In. (mm)	Wall Thk Mils (mm)
WST22	22	0 thru 9	250, 500, 1000, 2500, 10000	3	7/30	0.050 (1.27)	9 (0.23)
WST18	18	0 thru 9	250, 500, 1000, 2500, 5000	6.3	16/30	0.068 (1.73)	9 (0.23)



Features:

- Tinned Copper
- Tinned copper is more resistant to corrosion and easier to solder compared to bare copper
- UL re-spooled capabilities are available upon request
- Meets flammability rating VWI
- UL1061 176°F (80°C) 300V
- CSA IA 176°F (80°C) 300V
- 221°F (105°C) 600V
- MIL-W-16878/1 (22 ga only)
- 9 Mils, semi-rigid PVC

COLORS		
0 - Black	1 - Brown	2 - Red
3 - Orange	4 - Yellow	5 - Green
6 - Blue	7 - Violet	8 - Gray
9 - White		

UL Print Legend:

WST22: E56702 RU AWM STYLE 1061 **22** AWG 80C 300V VW-1 CSA LL67880 AWM I A 80C 300V FT-1 MIL-W-16878/1 TYPE B 0PB16 600V 105C

WST18: E56702 RU AWM STYLE 1061 **18** AWG 80C 300V VW-1 CSA LL67880 IA 80C 300V FT1

UNCONTROLLED DOCUMENT

All information provided by manufacturer
Subject to change
Updated 5/26/2011

www.waytekwire.com
Phone | 800.328.2724 | 952.949.0765
Fax | 800.858.0319 | 952.949.0965