

Electric Heat Guns

Proheat® PH-1100A Quick-Touch™ 3-Temp Heat Gun & Kit



PH A-Series
PH-1100A 3-Temp Heat Gun



3 Temperature and Airflow Settings (Low, Medium & High)

Low = 9 CFM & No Heat
 Medium = 9 CFM & 600°F (320°C)
 High = 18 CFM & 1200°F (650°C)




Quality attachments for professional applications

PH-1100A-00-K

Proheat 3-Temp heat gun with rugged storage case and 2 attachments (35016 & 35017)



Specifications

- **Motor:** Permanent Magnet
- **Nozzle Opening:** .88" I.D., 1.31" O.D.
- **Cordset:** 6', 2 Prong - Double Insulated
- **Dimensions:** 9.25" L x 3.43" W x 8.2" H
- 120V Models
- **Momentary Contact Switch** 
- **Tool Net Weight:** 1.9 lbs.
- **Shipping Weight Tool:** 3 lbs.
- **Shipping Weight Kit:** 10 lbs.

NOTE: Users should independently evaluate the suitability of the product for their application.

Proheat® PH-1100A Quick-Touch™ 3-Temp Heat Gun & Kit

Model No.	Air Temp	Air Volume				
PH-1100A	No Heat, 600°F, 1200°F	9 & 18 CFM	120V	50/60 Hz	13A	1560W
PH-1100A-00-K	PH-1100A Heat Gun with storage case and 2 attachments (35016 & 35017)					

Proheat PH-1100A Highlights

- Compact, lightweight, easy-to-use
- Trigger switch with trigger lock allows switch to be both momentary contact or locked in the on position
- Easy to replace plug-in element; takes just seconds to switch elements
- Easy to replace cordset; swap cord lengths in no time
- Easy connect nozzle covers; switch from traditional cover to a nozzle spacer quickly
- Base provides built-in stand for hands-free use
- Hanging loop located on top of heat gun
- Improved motor life; lab tested for 1000+ hrs
- Easy to repair; field repairable plug-in element, cord and user interface
- Make your Proheat even more versatile. See our wide variety of professional quality attachments and accessories (pages 13-14).