

- 2. RoHS COMPLIANT
- 3. MOISTURE RESISTANCE: IP68 (1M OF WATER FOR A PERIOD OF 24 HOURS , MATED CONDITION) IP69K (MATED CONDITION)
- 4. TEMPERATURE RANGE: -55°C~125°C
- 5. USE WITH CONNECTORS ATP04-6P* (* = MODIFICATIONS AND/OR COLORS)
- 6. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

	ATP04								
	IUMBEF	JMBER		DESCRIPTION				ITEM	
QUANTITY MATERIALS LIST									
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08 3) Note reference = MATERIAL SPECIFICATIONS:		SIGNATURES		DATE					
		DRAWN: LOUIE.YIN		19/OCT/20	Amphenol				
		CHECKED:	ORION.LI	20/OCT/20	Sine Systems - www.amphenol-sine.com				
		ENGINEER:			44724 Morley Drive Clinton Township, MI 48036				
		APPROVAL:	TOMMY.XIE	21/OCT/20	Giinton Township, Wil 40030				
		CUSTOMER:			6 POS,DUST CAP FOR RECEPTACLE,				
		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY, DESIGN FEATURES.			ATP SERIES				
PROCESS SPECIFICATIONS:		SPECIFICATIONS AND PERFORMANCE DASHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHO OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.		ORMANCE DATA ROPERTY OF ION. NO RIGHTS PLIED. ALL	A	C-	ATP04-6F	P-CAP	A1
NEXT ASS'Y:				NS.	SCALE: N	ONE		SHEET 1 OF	1