

## DCT110HIRK2

Article Number: 115-31100

Dual Clamp Tie - 150.0 lb, Stud Dia .25", Length 19.2", Max Bun Dia 2.3", PA66HIRHS, Black, 50/pkg



Download spec sheet

### Base Data

**Local Order Number** DCT110HIRK2

**Type** DCT11

**Color** Black (BK)

- Features and Benefits**
- Provides dual separation between bundles to prevent chaffing and abrasion.
  - 150 lb. tensile strength ensures enough strength for heavy duty applications.
  - Straps are releasable for increased serviceability.

**Product Description** HellermannTyton's dual clamp ties are designed to provide parallel separation between hoses, wires, cables and tubing, protecting them from abrasion. These ties have an optional mounting hole for securing bundles along the chassis of tracks, trailers, and heavy duty equipment. The unique one-piece design features the dual head centered on the strap.

**Fixation Method (FF)** Weld Stud Fixing

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Dual Clamp Tie - 150.0 lb, Stud Dia .25", Length 19.2", Max Bun Dia 2.3", PA66HIRHS, Black, 50/pkg

### Product Dimensions

**Minimum Tensile Strength (imperial)** 150.0 lbs

**Length L (imperial)** 19.2 "

**Length L (metric)** 489.0 mm

**Width W (imperial)** 0.5 "

**Width W (metric)** 12.7 mm

**Width W2 (imperial)** 0.7 "

**Width W2 (metric)** 19.7 mm

**Height H (imperial)** 0.8 "

**Height H (metric)** 19.1 mm

**Bundle Diameter min (imperial)** 0.2 "

**Bundle Diameter min (metric)** 6.4 mm

**Bundle Diameter max (imperial)** 2.3 "

**Bundle Diameter max (metric)** 58.0 mm

**Mounting Hole Diameter D (imperial)** 0.2 "

**Mounting Hole Diameter D (metric)** 6.2 mm

**Stud Size (Imperial)** .25 "

**Stud Size (Metric)** 6.35 mm

## Logistics and Packaging

---

**Quantity per** bag  
**Package Quantity** 50  
**Carton Quantity** 500 Pieces  
**Weight (Metric)** 12 kg

## Material and Specifications

---

**Material** Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)  
**Material Shortcut** PA66HIRHS  
**Flammability** UL94 HB  
**Operating Temperature** -40°F to +230°F (-40°C to +110°C)  
**ROHS Conformity** Yes