

47	7.3
	ioneriqm/A q8-\$0qTA








NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: N/A
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 25 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
 - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.7 RoHS COMPLIANT
- 4. MATING PART: ATP06-6S* PLUG. (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.
- 6 CONTACT SIZE AND REAR SEAL WIRE RANGE:


CONTACT SIZE	MIN. INSUL O.D.		TYPICAL WIRE RANGE
12	3.40 mm (.134 in)	4.95 mm (.195 in)	10 - 14 AWG




PART NUMBER CHART				
COLOR PART NUMBER				
GREY	ATP04-6P			
BLACK	ATP04-6P-BLK			

STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLOR (BLACK) IS AVAILABLE VIA SPECIAL ORDER.

		REVISIONS			
REV	ECO	DESCRIPTION	DATE	BY	APPR
A1	-	RELEASE DRAWING	24/AUG/19	PETER	TOMMY





	SEE PART N	JMBER C	CHART							
	PART NUMBER					DE	SCRIPTION		ITE	EM
QUANTITY MATERIALS LIST										
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC 10.30 Fractions ±1/64 2 PL DEC 20.30 Fractions ±1/64 Angles ±1* 3) Note reference = MATERIAL SPECIFICATIONS: PROCESS SPECIFICATIONS: NEXT ASSY:		SIGI	NATURES	_	Amphenol)			
		CHECKED:	PETER.YANG ORION.LI	24/AUG/19 24/AUG/19	<u> </u>				-	
		ENGINEER:			44724 Morley Drive Clinton Township, MI 48036					
		APPROVAL: CUSTOMER:	TOMMY.XIE	24/AUG/19	RECEPTACLE, 6 PIN, ATP SERIES					
		SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL		SIZE TYPE DWG NO: REVISI			ION			
				B SCALE: N	C- ONE	ATP04-6P	SHEET 1	A'	1	

DWG NO: ATP04-6P-XXX

RECEPTACLE, 6 PIN, ATP SERIES

S-XXX REV: A1 SH: