


Article Number: 121322

## 13P/12V 100% waterproof «JAEGER Expert» Socket (ISO 11446)



|            |               |
|------------|---------------|
| Categories | Socket        |
| Standards  | ISO 11446     |
| Industries | Cars          |
| Brand      | JAEGER Expert |

### Electrical Details and Temperature Resistance

|                |    |
|----------------|----|
| Voltage [in V] | 12 |
|----------------|----|

### Packaging and Order Details

|                                        |                                                                  |
|----------------------------------------|------------------------------------------------------------------|
| Accessories (to be ordered separately) | 037752                                                           |
| Included in delivery                   | contact insert , contacts , cover cap , seal , single wire seals |
| Included in the scope of delivery      | 383085,382598,053861-4,052675-4,026988                           |
| Packaging                              | retail bag                                                       |

### Design Features

|                 |                 |
|-----------------|-----------------|
| Design/Version  | built-in socket |
| Special feature | built-in socket |
| Type of seal    | seal            |

### Miscellaneous

|                    |                 |
|--------------------|-----------------|
| Product supplement | 100% waterproof |
|--------------------|-----------------|

### Material

|                      |                      |
|----------------------|----------------------|
| Contact insert color | black                |
| Contact surface      | nickel (Ni)          |
| Cover material       | reinforced composite |
| Housing color        | black                |
| Housing material     | reinforced composite |

### Connectivity

|                     |                                        |
|---------------------|----------------------------------------|
| Cable outlet        | seal can be positioned in steps of 30° |
| Contact termination | crimp contact                          |
| No. of poles        | 13                                     |

### Norms and Standards

|            |                        |
|------------|------------------------|
| Protection | IP 54 , IP X7 , IP X9K |
|------------|------------------------|