



## NOTES:

1. ALL STEEL PARTS PLATED
2. ALL DIMENSIONS REFERENCE ONLY
3. SILVER CONTACT SURFACES
4. RATING:

CONTINUOUS-175 AMPS, 6-12-24-36 VDC  
 INTERMITTENT-800 AMPS, 6-12-24-36 VDC  
 15 SECONDS ON, 5 MINUTES OFF, IGNITION PROTECTED

METRIC

Revision Control Record				Rev.	Description of Change	ECN No.	Date	Tolerances: Unless otherwise specifically noted, the following are default tolerances:			PROPRIETARY INFORMATION This Engineering Drawing, and the information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.	Special Characteristics:		 <b>Cole Hersee Co.</b> 30 Old Colony Ave., South Boston, MA, 02127 Fax: 617-268-2108 Web: www.colehersee.com
Rev.	Description of Change	ECN No.	Date					2-places +/- 0.02"	3-places +/- 0.005"	Angular +/- 1°		<input type="checkbox"/> Critical Characteristic, relating to Safety and/or Regulatory Compliance <input checked="" type="checkbox"/> Process Control <input checked="" type="checkbox"/> Significant Characteristic relating to Functionality <input type="checkbox"/> Control Dimension relating to Form-Fit - Function as defined by Cole Hersee Company and/or the Customer	Description:	
H	UPDATED DRAWING FORMAT UPDATED LABEL	10016	01/13/10											<b>SWITCH, MASTER DISCONNECT</b> Drawing / Part No.: <b>2484-16</b> H