

Product

MCT FRAME



MCT FRAME is a crimping tool frame for mobile tool die sets. Easily interchangeable crimp dies are kept together with a special pin to simplify handling. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap

The part number is a reference to the frame without dies.

TECHNICAL DATA
Length: 234 mm/9.21"
Width: 31 mm/1.22"
Height: 64 mm/2.52"
Weight: 460 gr/1.23 lb
Life span, cycles: 20,000




Mobile tool/4300-3128/ AAA


Mobile die set for insulated connectors (green, yellow). This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap.

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.



DIE PROFILE



CRIMP PROFILE


TECHNICAL DATA
Length: 29 mm/1.14"
Width: 18 mm/0.71"
Height: 39 mm/1.54"
Weight: 66 gr/0.15 lb
Wire size: 0.1-6 mm² / AWG 26-
AWG 10
Crimp dimensions mm/ mm²:
0,1 - 0,4 / 4 - 6
Crimp dimensions inch/ AWG:
26 - 22/ 12 - 10
Life span, cycles: 20,000



Mobile tool/4300-3129/ AAA

Mobile die set for insulated connectors (red, blue). This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use,



DIE PROFILE



CRIMP PROFILE

TECHNICAL DATA
Length: 29 mm/1.14"
Width: 9.5 mm/0.37"
Height: 39 mm/1.54"
Weight: 75 gr/0.17 lb
Wire size: 0.5-2.5 mm² / AWG 22-
AWG 14
Crimp dimensions mm/ mm²:
0,5 - 1,5 / 1,5 - 2,5
Crimp dimensions inch/ AWG:
22 - 16/ 16 - 14
Life span, cycles: 20,000

also for outdoor operations in all weather conditions

- Hole in handle allows attachment of safety strap

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.




Mobile tool/4300-3147/ AAA


Mobile die set for Turned pin connectors, 0,14-4 mm². This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.



DIE PROFILE



CRIMP PROFILE

TECHNICAL DATA

Length: 29 mm/1.14"

Width: 10 mm/0.39"

Height: 39 mm/1.54"

Weight: 72 gr/0.16 lb

Wire size: 0.14-4 mm² / AWG 26-AWG 12

Crimp dimensions mm/ mm²:

0,14 - 1,0 / 1,5 / 2,5 / 4

Crimp dimensions inch/ AWG:

16 - 18/ 16/ 14/ 12

Life span, cycles: 20,000




Mobile tool/4300-3148/ AAA


Mobile die set for Turned pin connectors
6-10 mm²

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. Following plugs are also available:



DIE PROFILE



CRIMP PROFILE

TECHNICAL DATA


Length: 29 mm/1.14"
Width: 10 mm/0.39"
Height: 39 mm/1.54"
Weight: 66 gr/0.15 lb
Wire size: 6-10 mm² / AWG 10-
AWG 8
Crimp dimensions mm/ mm²:
6 /10
Crimp dimensions inch/ AWG:
10/ 8
Life span, cycles: 20,000



Mobile tool/4300-3139/ AAA

Mobile die set for non insulated connectors
4-10 mm². This is one of the interchangeable
crimp die sets for the MCT frame. A wide range
of crimp dies enables the user to cover all
applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use,



DIE PROFILE



CRIMP PROFILE

TECHNICAL DATA

Length: 32 mm/1.26"
Width: 10 mm/0.39"
Height: 39 mm/1.54"
Weight: 60 gr/0.13 lb
Wire size: 4-10 mm² / AWG 12-
AWG 8
Crimp dimensions mm/ mm²:
4 /6 /10
Crimp dimensions inch/ AWG:
12/ 10/ 8
Life span, cycles: 20,000

also for outdoor operations in all weather conditions

- Hole in handle allows attachment of safety strap

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame




Mobile tool/4300-3137/ AAA


Mobile die set for non insulated connectors 0,75-2,5 mm². This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.



DIE PROFILE



CRIMP PROFILE

TECHNICAL DATA

Length: 31 mm/1.22"

Width: 8 mm/0.31"

Height: 39 mm/1.54"

Weight: 68 gr/0.15 lb

Wire size: 0.75-2.5 mm² / AWG

20- AWG 14

Crimp dimensions mm/ mm²:

0,75 /1,5 /2,5

Crimp dimensions inch/ AWG:

20/ 16/ 14

Life span, cycles: 20,000




Mobile tool/4300-3136/ AAA


Mobile die set for coaxial connectors RG 58, 59, 62, 71 BNC/ TNC. This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.



DIE PROFILE



CRIMP PROFILE


TECHNICAL DATA
 Length: 30 mm/1.18"
 Width: 10 mm/0.39"
 Height: 39 mm/1.54"
 Weight: 72 gr/0.16 lb
 Crimp dimensions mm/ mm²:
 1,69 HEX/5,41 HEX/6,48 HEX
 Crimp dimensions inch/ AWG:
 .067\W.213\W.255\W
 Life span, cycles: 20,000
 Cables: RG108A/ U, RG142B/ U,
 RG210/ U, RG223/ U, RG302/ U,
 RG58C/ U, RG59B/ U, RG62A/ U,
 RG62B/ U, RG71B/ U



Mobile tool/4300-3142/ AAA

Mobile die set for non insulated connectors 0,5-6 mm². This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.



DIE PROFILE



CRIMP PROFILE

TECHNICAL DATA
 Length: 29 mm/1.14"
 Width: 8 mm/0.31"
 Height: 39 mm/1.54"
 Weight: 67 gr/0.15 lb
 Wire size: 0.5-6 mm² / AWG 22-
 AWG 10
 Crimp dimensions mm/ mm²:
 0,5 - 2,5 / 4 - 6
 Crimp dimensions inch/ AWG:
 22 - 14/ 12 - 10
 Life span, cycles: 20,000

- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.




Mobile tool/4300-3127/ AAA


Mobile die set for endsleeves 0,25-10 mm². This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.



DIE PROFILE



CRIMP PROFILE

TECHNICAL DATA
 Length: 31 mm/1.22"
 Width: 12 mm/0.47"
 Height: 39 mm/1.54"
 Weight: 86 gr/0.19 lb
 Wire size: 0.25-10 mm² / AWG 24-
 AWG 8
 Crimp dimensions mm/ mm²:
 0,25 - 0,75 / 1,0 - 1,5 / 2,5 / 4 / 6 / 10
 Crimp dimensions inch/ AWG:
 24 - 20/ 18 - 16/ 14/ 12/ 10/ 8
 Life span, cycles: 20,000




Mobile tool/4300-3153/ AAA


Mobile die set for endsleeves 16-25 mm². This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.



DIE PROFILE



CRIMP PROFILE


TECHNICAL DATA
 Length: 29 mm/1.14"
 Width: 14.5 mm/0.57"
 Height: 39 mm/1.54"
 Weight: 87 gr/0.19 lb
 Wire size: 16-25 mm² / AWG 6-
 AWG 4
 Crimp dimensions mm/ mm²:
 16 /25
 Crimp dimensions inch/ AWG:
 6/ 4
 Life span, cycles: 20,000



Mobile tool/4300-3154/ AAA

Mobile die set for endsleeves 35-50 mm². This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use,



DIE PROFILE



CRIMP PROFILE

TECHNICAL DATA
 Length: 34 mm/1.34"
 Width: 18 mm/0.71"
 Height: 39 mm/1.54"
 Weight: 86 gr/0.19 lb
 Wire size: 35-50 mm² / AWG 2-
 AWG 0
 Crimp dimensions mm/ mm²:
 35 /50
 Crimp dimensions inch/ AWG:
 2/ 0
 Life span, cycles: 20,000

also for outdoor operations in all weather conditions

- Hole in handle allows attachment of safety strap

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.




Mobile tool/4300-3150/ AAA

Mobile die set for non insulated open barrel connectors 0,1-1 mm². This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.



DIE PROFILE



CRIMP PROFILE

TECHNICAL DATA

Length: 29 mm/1.14"
Width: 6 mm/0.24"
Height: 39 mm/1.54"
Weight: 72 gr/0.16 lb
Wire size: 0.1-1 mm² / AWG 26-
AWG 18
Crimp dimensions mm/ mm²:
0,1 - 0,25 / 0,25 - 0,5 / 0,5 - 1,0
Crimp dimensions inch/ AWG:
26 - 24/ 24 - 22/ 22 - 18
Life span, cycles: 20,000




Mobile tool/4300-3151/ AAA

Mobile die set for non insulated open barrel connectors 0,5-2,5 mm². This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.



DIE PROFILE



CRIMP PROFILE


TECHNICAL DATA
 Length: 29 mm/1.14"
 Width: 7 mm/0.28"
 Height: 39 mm/1.54"
 Weight: 63 gr/0.14 lb
 Wire size: 0.5-2.5 mm² / AWG 22- AWG 14
 Crimp dimensions mm/ mm²:
 0,5 - 1,0 / 1,5 - 2,5
 Crimp dimensions inch/ AWG:
 22 - 16/ 16 - 14
 Life span, cycles: 20,000



Mobile tool/4300-3146/ AAA

Mobile die set for non insulated open barrel connectors 0,5-6 mm². This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.



DIE PROFILE



CRIMP PROFILE

TECHNICAL DATA
 Length: 29 mm/1.14"
 Width: 10 mm/0.39"
 Height: 39 mm/1.54"
 Weight: 74 gr/0.16 lb
 Wire size: 0.5-6 mm² / AWG 22- AWG 10
 Crimp dimensions mm/ mm²:
 0,5 - 1,5 / 1,5 - 2,5 / 4 - 6
 Crimp dimensions inch/ AWG:
 22 - 16/ 16 - 14/ 12 - 10
 Life span, cycles: 20,000

- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.




Mobile tool/4300-3141/ AAA


Mobile die set for coaxial-/ Fiberoptic: ST, SC, SMA, SMB, SFR. This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap.

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.



DIE PROFILE



CRIMP PROFILE

TECHNICAL DATA
 Length: 34 mm/1.34"
 Width: 10 mm/0.39"
 Height: 39 mm/1.54"
 Weight: 76 gr/0.17 lb
 Crimp dimensions mm/ mm²:
 3,25 HEX/3,84 HEX/4,52
 HEX/5,41 HEX
 Crimp dimensions inch/ AWG:
 .128\W/.151\W/.178\W/.213\W
 Life span, cycles: 20,000




Mobile tool/4300-3140/ AAA


Mobile die set for coaxial connectors: RG 174, RG 179/ BNC/ TNC. This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap.

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.



DIE PROFILE



CRIMP PROFILE

TECHNICAL DATA


Length: 29 mm/1.14"
 Width: 10 mm/0.39"
 Height: 39 mm/1.54"
 Weight: 73 gr/0.16 lb
 Crimp dimensions mm/ mm²:
 0,7 Sqr./1,69 HEX/3,25 HEX/4,52 HEX
 Crimp dimensions inch/ AWG:
 .028\1\,067\1\,128\1\,178\1\
 Life span, cycles: 20,000
 Cables: RG122/ U, RG174A/ U,
 RG179B/ U, RG180B/ U, RG187A/
 U, RG188A/ U, RG279/ U, RG303/
 U, RG316/ U




Mobile tool/4300-3138/ AAA

Mobile die set for coaxial connectors: CATV RG 6,59. This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.



DIE PROFILE



CRIMP PROFILE

TECHNICAL DATA

Length: 34 mm/1.34"
 Width: 10 mm/0.39"
 Height: 39 mm/1.54"
 Weight: 79 gr/0.17 lb
 Crimp dimensions mm/ mm²:
 8,23 HEX/9,14 HEX
 Crimp dimensions inch/ AWG:
 .324\1\,360\1\
 Life span, cycles: 20,000
 Cables: 1695, RG 6, RG143A/ U,
 RG212/ U, RG222/ U, RG6 Quad,
 RG6A/ U, TWINAX

- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.




Mobile tool/4300-3144/ AAA

Mobile die set for RJ45 connectors 8/8, 8/6, 8/4. This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap.

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.



DIE PROFILE

TECHNICAL DATA
 Length: 29 mm/1.14"
 Width: 17 mm/0.67"
 Height: 39 mm/1.54"
 Weight: 42 gr/0.09 lb
 Crimp dimensions mm/ mm²:
 RJ 45
 Crimp dimensions inch/ AWG:
 RJ 45
 Life span, cycles: 20,000




Mobile tool/4300-3132/ AAA

Mobile die set for RJ11 connectors 6/6, 6/4. This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.



DIE PROFILE


TECHNICAL DATA
Length: 29 mm/1.14"
Width: 14 mm/0.55"
Height: 39 mm/1.54"
Weight: 60 gr/0.13 lb
Crimp dimensions mm/ mm²:
RJ 11
Crimp dimensions inch/ AWG:
RJ 11
Life span, cycles: 20,000



Mobile tool/4300-3262/ AAA

Mobile die set for insulated heat shrink butt splice connectors (green, yellow). This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.



DIE PROFILE



CRIMP PROFILE

TECHNICAL DATA
Length: 29 mm/1.14"
Width: 10 mm/0.39"
Height: 39 mm/1.54"
Weight: 65 gr/0.14 lb
Wire size: 0.32-6 mm² / AWG 22-
AWG 10
Crimp dimensions mm/ mm²:
0,32 - 0,75 /4 - 6
Crimp dimensions inch/ AWG:
22 - 18/ 12 - 10
Life span, cycles: 20,000

- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap.

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.




Mobile tool/4300-3258/ AAA


Mobile die set for insulated heat shrink butt splice connectors (red, blue). This is one of the interchangeable crimp die sets for the MCT frame. A wide range of crimp dies enables the user to cover all applications in just one tool frame.

- Reliable – crimping performance is consistent and accurate with a parallel action stroke.
- Easy to use – designed to give the user full visibility of the crimping process. Handles are shaped for low effort crimping with a one or two hand grip.
- Versatile – an easy- access release function allows fast and simple exchange of crimp dies. No special tools needed.
- Weight and size of the tool are optimized to make it easy to carry. Dies are kept in pairs and delivered in a modular reusable box.
- Comfortable – the entire tool frame is covered in smooth plastic for comfortable use, also for outdoor operations in all weather conditions
- Hole in handle allows attachment of safety strap

Tool shown is the frame without a die, for correct die profile please look at the illustration to the right. The part number is a reference to the die set without frame.



DIE PROFILE



CRIMP PROFILE

TECHNICAL DATA
 Length: 29 mm/1.14"
 Width: 10 mm/0.39"
 Height: 39 mm/1.54"
 Weight: 66 gr/0.15 lb
 Wire size: 0.5-2.5 mm² / AWG 22-
 AWG 14
 Crimp dimensions mm/ mm²:
 0,5 - 1,5 / 1,5 - 2,5
 Crimp dimensions inch/ AWG:
 22 - 16/ 16 - 14
 Life span, cycles: 20,000