

# CABLE TIES



Type 21  
AH-2  
Positioning  
Device



Type 11 Positioning Device

SAE AS23190  
Mil-Spec Approved  
AS33671



## Miniature 18 lb. Cable Ties

Per Bag	Waytek Part Number	Color & Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Case
1,000	21021M	Natural	4.12/104.77	.095/2.413	.042/1.066	18 lb. 80 n.	.874/22.2	UL-CSA MS3367-4*	10,000
100	21021C	Nylon							
1,000	21041M	UV Black	6.18/157.14	.095/2.413	.042/1.066	18 lb. 80 n.	1.50/38.1	UL-CSA	10,000
100	21041C	Nylon							
1,000	21022M	Natural	8.18/207.94	.095/2.413	.042/1.066	18 lb. 80 n.	2.187/55.5	UL-CSA	10,000
100	21022C	Nylon							
1,000	21042M	UV Black	8.18/207.94	.095/2.413	.042/1.066	18 lb. 80 n.	2.187/55.5	UL-CSA	10,000
100	21042C	Nylon							
1,000	21018M	Natural	8.18/207.94	.095/2.413	.042/1.066	18 lb. 80 n.	2.187/55.5	UL-CSA	10,000
100	21018C	Nylon							
1,000	21019M	UV Black	8.18/207.94	.095/2.413	.042/1.066	18 lb. 80 n.	2.187/55.5	UL-CSA	10,000
100	21019C	Nylon							

Tolerance: .xxx = +-.005, .xx = +-.015, Fraction = +-1/32" ROHS compliant

## Intermediate 40 lb. Cable Ties

Per Bag	Waytek Part Number	Color & Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Case
1,000	21023M	Natural	5.84/148.33	.140/3.556	.049/1.244	40 lb. 178 n.	1.437/36.4	UL-CSA MS3367-5*	10,000
100	21023C	Nylon							
1,000	21043M	UV Black	8.875/225.42	.140/3.556	.049/1.244	40 lb. 178 n.	2.375/60.3	UL-CSA	10,000
100	21043C	Nylon							
1,000	21073M	Natural	10.96/278.58	.140/3.556	.054/1.371	40 lb. 178 n.	3.375/85.7	UL-CSA	5,000
100	21073C	Nylon							
1,000	21093M	UV Black	14.25/361.95	.140/3.556	.054/1.371	40 lb. 178 n.	4.00/101.6	UL-CSA	5,000
100	21093C	Nylon							
1,000	21074M	Natural	14.25/361.95	.140/3.556	.054/1.371	40 lb. 178 n.	4.00/101.6	UL-CSA	5,000
100	21074C	Nylon							
1,000	21094M	UV Black	14.25/361.95	.140/3.556	.054/1.371	40 lb. 178 n.	4.00/101.6	UL-CSA	5,000
100	21094C	Nylon							
100	21075C	Natural Nylon	14.25/361.95	.140/3.556	.054/1.371	40 lb. 178 n.	4.00/101.6	UL-CSA	5,000
100	21095C	UV Black Nylon							

Tolerance: .xxx = +-.005, .xx = +-.015, Fraction = +-1/32" ROHS compliant

## Standard 50 lb. Cable Ties

Per Bag	Waytek Part Number	Color & Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Case
1,000	21024M	Natural	7.56/192.07	.180/4.572	.052/1.320	50 lb. 222 n.	1.875/47.6	UL-CSA MS3367-1*	10,000
100	21024C	Nylon							
1,000	21044M	UV Black	11.25/285.75	.180/4.572	.052/1.320	50 lb. 222 n.	3.062/77.7	UL-CSA MS3367-7*	5,000
100	21044C	Nylon							
100	21025C	Natural Nylon	14.25/361.95	.180/4.572	.052/1.320	50 lb. 222 n.	4.00/101.6	UL-CSA MS3367-2*	5,000
100	21045C	UV Black Nylon							
100	21026C	Natural Nylon	14.25/361.95	.180/4.572	.052/1.320	50 lb. 222 n.	4.00/101.6	UL-CSA MS3367-2*	5,000
100	21046C	UV Black Nylon							

Tolerance: .xxx = +-.005, .xx = +-.015, Fraction = +-1/32" ROHS compliant

**All products are manufactured by Advanced Cable Ties, INC.**

## Heavy Duty 120 lb. Cable Ties

Per Bag	Waytek Part Number	Color & Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Case
100	21570	Natural Nylon	8.70/220.98	.300/7.620	.076/1.930	120 lb. 534 n.	2.06/52.3	UL-CSA	3,000
100	21590	UV Black Nylon							
100	21027	Natural Nylon	15.09/383.36	.300/7.620	.076/1.930	120 lb. 534 n.	4.06/103.1	UL-CSA MS3367-3*	2,000
100	21047	UV Black Nylon							
50	21017	Natural Nylon	24.50/622.30	.302/7.670	.083/2.108	120 lb. 534 n.	7.00/177.8	UL-CSA	500
50	21016	UV Black Nylon							
50	21003	Natural Nylon	30.87/784.22	.302/7.670	.083/2.108	120 lb. 534 n.	9.00/228.6	UL-CSA MS3367-6*	500
50	21004	UV Black Nylon							

Tolerance: .xxx = +/-0.005, .xx = +/-0.015, Fraction = +/-1/32" ROHS compliant

## Extra Heavy Duty 175 lb. Cable Ties

Per Bag	Waytek Part Number	Color & Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Case
50	21072	Natural Nylon	25.25/641.35	.340/8.636	.090/2.286	175 lb. 778 n.	7.18/182.56	UL-CSA MS3367-10	500
50	21092	UV Black Nylon							
50	21578	Natural Nylon	37.25/946.15	.340/8.636	.090/2.286	175 lb. 778 n.	11.00/279.40	UL-CSA MS3367-13	500
50	21598	UV Black Nylon							
50	21579	Natural Nylon	48.50/1231.9	.340/8.636	.090/2.286	175 lb. 778 n.	14.50/368.30	UL-CSA MS3367-16	500
50	21599	UV Black Nylon							

Tolerance: .xxx = +/-0.005, .xx = +/-0.015, Fraction = +/-1/32" ROHS compliant



Per Bag	Waytek Part Number	Color	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	Mil-Spec	Per Case
100	21501	Brown	4.12/104.77	.095/2.413	.042/1.066	18 lb. 80 n.	.874/22.2	MS3367-4-1	10,000
	21502	Red						MS3367-4-2	
	21503	Orange						MS3367-4-3	
	21504	Yellow						MS3367-4-4	
	21505	Green						MS3367-4-5	
	21506	Blue						MS3367-4-6	
	21507	Purple						MS3367-4-7	
	21508	Gray						MS3367-4-8	
	21512	Fluorescent Pink							
	21513	Fluorescent Orange							
	21514	Fluorescent Yellow							
	21515	Fluorescent Green							
100	21521	Brown	7.56/192.07	.180/4.572	.052/1.320	50 lb. 222 n.	1.875/47.6	MS3367-1-1	5,000
	21522	Red						MS3367-1-2	
	21523	Orange						MS3367-1-3	
	21524	Yellow						MS3367-1-4	
	21525	Green						MS3367-1-5	
	21526	Blue						MS3367-1-6	
	21527	Purple						MS3367-1-7	
	21528	Gray						MS3367-1-8	
	21532	Fluorescent Pink							
	21533	Fluorescent Orange							
	21534	Fluorescent Yellow							
	21535	Fluorescent Green							

Tolerance: .xxx = +/-0.005, .xx = +/-0.015, Fraction = +/-1/32". UL Listed for Air Handling Spaces. CSA approved. ROHS compliant

**All products are manufactured by Advanced Cable Ties, INC.**



## Mounting Hole Cable Ties

Per Bag	Waytek Part Number	Color & Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Screw Size	Diameter Inch/mm	Hole Diameter Inch/mm	Per Case
1,000	21031M	Natural	5.8/149.2	.138/3.505	.045/1.143	40 lb. 178 n.	#8	1.25/31.75	.175/4.44	10,000
100	21031C	Nylon								
1,000	21051M	UV Black	5.8/149.2	.138/3.505	.045/1.143	40 lb. 178 n.	#8	1.25/31.75	.175/4.44	10,000
100	21051C	Nylon								
1,000	21032M	Natural	8.0/203.2	.177/4.495	.052/1.320	50 lb. 222 n.	#10	1.75/44.45	.208/5.28	5,000
100	21032C	Nylon								
1,000	21052M	UV Black	8.0/203.2	.177/4.495	.052/1.320	50 lb. 222 n.	#10	1.75/44.45	.208/5.28	5,000
100	21052C	Nylon								
100	21033C	Natural Nylon	11.5/292.1	.177/4.495	.053/1.346	50 lb. 222 n.	#10	3.00/76.20	.206/5.23	5,000
100	21053C	UV Black Nylon								
100	21034C	Natural Nylon	14.5/368.3	.177/4.495	.053/1.346	50 lb. 222 n.	#10	4.00/101.60	.206/5.23	5,000
100	21054C	UV Black Nylon								
100	21545	Natural Nylon	15.7/400.0	.298/7.569	.075/1.905	120 lb. 534 n.	1/4"	4.06/103.17	.256/6.50	2,000
100	21555	UV Black Nylon								

Tolerance: .xxx = +/- .005, .xx = +/- .015, Fraction = +/- 1/32" 5" Mounting Hole ties are made in TW. ROHS compliant

## Low Profile Cable Ties

Per Bag	Waytek Part Number	Color & Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Case
100	21248	Natural Nylon	7.5/190.5	.176/4.470	.053/1.346	50 lb. 222 n.	1.75/44.45	UL-CSA MS3367-23	10,000
100	21249	UV Black Nylon							
100	21259	UV Black Nylon	16.0/406.4	.296/7.530	.075/1.905	120 lb. 534 n.	4.06/103.17	UL-CSA MS3367-25	2,000

Tolerance: .xxx = +/- .005, .xx = +/- .015, Fraction = +/- 1/32" ROHS compliant

## Rubber Adhesive Mounting Pads

Per Bag	Waytek Part Number	Color & Material	Length Inch/mm	Height Inch/mm	Slot Height Inch/mm	Slot Width Inch/mm	Screw Size	FU-CSA Mil-Spec	Per Case
100	21240	Natural Nylon	.74/18.79	.19/4.82	.05/1.27	.20/5.08	#4	FU-CSA	1,000
100	21040	Natural Nylon	.99/25.14	.20/5.08	.06/1.52	.20/5.08	#6	FU-CSA	1,000

Tolerance: .xxx = +/- .005, .xx = +/- .015, Fraction = +/- 1/32" ROHS compliant

## Screw Mounts

Per Bag	Waytek Part Number	Color & Material	Length Inch/mm	Height Inch/mm	Width Inch/mm	Slot Height Inch/mm	Slot Width Inch/mm	Screw Size	UL-CSA Mil-Spec	Per Case
100	21252	Natural Nylon	.90/22.8	.38/9.6	.63/16.0	.12/3.1	.30/7.6	1/4"	UL-CSA	1,000
100	21251	Natural Nylon	.90/23.0	.35/9.0	.63/16.0	.12/3.1	.35/9.0	#10		1,000

Tolerance: +/- .03"/.76mm ROHS compliant

All products are manufactured by **Advanced Cable Ties, INC.**

**1-800-328-2724**  
**www.waytekwire.com**

Uncontrolled Document  
 Last Revision: 01.21.20