## **7-POLE SOCKETS**

- Meets and exceeds all standards of SAEJ560 (SAE applies only to solid pins)
- Floating pins for ease of alignment and maximum contact.
- Optimum slant mount and drain slot rid housing interior of accumulated moisture.
- Will accept the widest range of gauges from #16 wires to #8 ground wire. Ground Terminal Pin #1 will accept #14 gauge min. to #8 gauge max. Other terminals will accept #16 gauge min. to #10 gauge max.
- 40 Amps continuous duty @ 6-28 VDC.
- Self grounded. (Zinc Die-Cast Units Only) to #1 Ground Terminal.
- Stainless steel spring.
- Recommended Mounting Hole is 2" diameter
- *Interchangeable with competitive makes.*

No.	Color	Wire Gauge	FMVSS- 121 Anti- Lock Gauge	Circuit
1	White	10	8	Ground Return
2	Black	12	12	Clearance, Side Marker and Identification Lamps
3	Yellow	12	12	Left Turn & Hazard Signal
4	Red	12	10	Stop Lamps & Anti-Lock Devices
5	Green	12	12	Right Turn Signal & Hazard Signal
6	Brown	12	12	Tail, Rear Clearance Marker, License Plate Lamp
7	Blue	12	12	Auxiliary Circuit / ABS Power

## WIRE INSERTION STYLE SOCKETS



11-72 Solid 3 hole 11-Sp 3 h

Solid Pin 3 hole mount

> 11-730 Split Pin 3 hole mount

## POLLA/GLASS GLASS FILLED NYLON

11-724 Nylon socket Split Pin 11-723 Nylon socket Solid Pin



## **ACCESSORIES**

11-761
7 Pole Socket
Rubber Socket Boot
for 11-720,11-721, 11723, 11-724, 11729,11-730 and 11851; seals against dust
and moisture, 1.5"
long. For .460-.720
diameter cable.

FOR DRAINAGE



11-780 Neoprene rubber gasket for 3 hole mount die-cast sockets. May be used as template

11-773 Same as 11-780 except for 2 hole mount sockets.



**11-771**7-Pole Socket bracket.
Fits all 7-Pole Sockets including 11-851.



11-777 Hardware Kit for 7-Pole Plugs (except RV)

11-781 Hardware Kit for 7-Pole Zinc Die-Cast Socket 11-779 Hardware Kit for 7-Pole Molded Pollak/Glass Sockets