APEX® 2.8 SEALED SERIES



BENEFITS

- Heavy-duty performance
- Highest current rating
- Ergonomic design

FEATURES

- Most compact 2.8 mm system in the industry
- Fully protected interface seal
- Meets or exceeds USCAR performance standards and GMW3191
- Compliant with USCAR design guidelines and performance standards
- 0.75 mm² (20 AWG) to 4 mm² (10 AWG)
- Primary Lock Reinforcement (PLR)
- Mechanical polarization

AVAILABLE CONFIGURATIONS


Cavity Count (ways)	2, 3, 4, 5, 6, 10, 14
Cavity Configurations (mm)	2.8
Genders	Female, Male
Sealing Type	Mat Sealed
Centerline Spacing (mm)	5.25



APPLICATIONS

Sealed inline and device applications

See back page for representative part numbers and packaging dimensions.







About Aptiv

Aptiv is a global technology company that develops safer, greener and more connected solutions enabling a more sustainable future of mobility.

Visit aptiv.com



Cavity count	Blade size (mm)	Gender	Dimensions W x H x D (mm)	Part number	Index	Color	Other indexes offered
2	2.8	F	24.8 x 25.7 x 40.1	10757672	А	Black	B, C, D
2	2.8	М	21.9 x 23.4 x 53.0	15488574	А	Black	B, C, D
3	2.8	F	28.2 x 21.9 x 40.1	10757671	А	Black	B, C, D
3	2.8	М	28.2 x 22.5 x 53.0	15394689	А	Black	B, C, D
4	2.8	F	32.6 x 22.2 x 40.1	15425692	А	Black	B, C, D
4	2.8	М	31.1 × 22.5 × 53.0	15489820	А	Black	B, C, D
5	2.8	F	36.0 x 23.4 x 41.3	33513170	А	Black	B, C, D
6	2.8	F	24.8 x 25.3 x 37.7	35063643	А	Black	B, C, D
6	2.8	М	24.4 x 26.3 x 53.0	15430633	А	Black	B, C, D
10	2.8	F	35.3 x 31.4 x 40.1	15316895	А	Black	B, C, D
10	2.8	М	32.4 x 29.1 x 53.0	15425612	Α	Black	B, C, D
14	2.8	F	45.8 x 30.8 x 37.8	10763414	Α	Black	B, C, D
14	2.8	М	46.2 x 29.2 x 53.1	10757674	А	Black	B, C, D

Please, contact an Aptiv representative for the full part number list.

COMPATIBLE SEALS

Туре	Applicable Wire Size (mm²)	Color	Restraint Ring	Part Number
			9 M	
Cable Seal	0.35 - 1.0	Pink	Yes	35296484
Cable Seal	1.0 - 2.0	Black	Yes	15518641
Cable Seal	2.5 - 4.0	Brown	Yes	15458498
Cavity Plug	N/A	Blue	Yes	35478080
Cavity Plug	N/A	White	No	15305170



DIMENSION MEASUREMENT SAMPLE



EXPLODED VIEW









APEX® 2.8 Sealed 10W Female

APEX® 2.8 Sealed 10W Female

APEX® 2.8 Sealed 10W Male

APEX® 2.8 Sealed 10W Female

APEX® 2.8 Sealed 10W Male

COMPATIBLE WITH



APEX® 2.8 Series Terminals

Part numbers, specifications, dimensions and performance data in this document are for general references only and are subject to change without notice. To verify product information, please contact an Aptiv representative.



