

# TECHNICAL DATA SHEET

**Part Number** SNP7GHS0C2  
**Article No.** 192-10070  
**Type** SNP7



The Snapper Hose Clamp features a ratchet-style closure for reduced assembly time. It can be added after connection of the hose. Release by sliding the ratchet ends apart. Snappers can be used in under-hood applications and are stable in a wide variety of chemicals including salts, bases, alcohols, ethers, detergents, gasoline, lubricating oils and greases. They are manufactured in black PA66 glass filled, impact modified, heat stabilized material. Custom design and color options are available based upon application and volume requirements.

|                              |                                                                       |
|------------------------------|-----------------------------------------------------------------------|
| <b>Material</b>              | Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13) |
| <b>Operating Temperature</b> | -40°F to +257°F (-40°C to +125°C)                                     |
| <b>Flammability</b>          | UL 94 HB                                                              |
| <b>UV Resistant</b>          | No                                                                    |
| <b>Use Conditions</b>        | For Indoor and Outdoor Use                                            |
| <b>Color</b>                 | Black (BK)                                                            |

|                       |            |
|-----------------------|------------|
| <b>Pkg. Qty.</b>      | 100        |
| <b>Carton Qty.</b>    | 6000       |
| <b>Customs Number</b> | 3926909988 |

|                                        |                  |
|----------------------------------------|------------------|
| <b>Bundle Diameter Max. (imperial)</b> | 0.54 "           |
| <b>Bundle Diameter Max. (metric)</b>   | 13.7 mm          |
| <b>Bundle Diameter Min. (imperial)</b> | 0.45 "           |
| <b>Bundle Diameter Min. (metric)</b>   | 11.4 mm          |
| <b>Fixation Method</b>                 | Plug-in mounting |
| <b>Max. Width (imperial)</b>           | 1.131 "          |
| <b>Max. Width (metric)</b>             | 28.5 mm          |
| <b>Min. Width (imperial)</b>           | 0.733 "          |
| <b>Min. Width (metric)</b>             | 18.4 mm          |
| <b>Wall Thickness (imperial)</b>       | 0.068 "          |
| <b>Wall Thickness (metric)</b>         | 1.7 mm           |

