



- NOTES:
 1. HOLDER MATERIAL : PVC NATURAL COLOR.
 2. WIRE : 1015 12AWG RED.
 3. RATING : MAX. 30A, 32VDC.
 4. FUSEHOLDERS SHOULD NOT BE PLACED UNDER TENSION IN FINAL APPLICATION

METRIC
ASSEMBLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN BRACKETS [] ARE INCHES
 UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.
 © DENOTES CRITICAL CHARACTERISTICS.
 CPK DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE
 ST DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS
 CP DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE

NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-

COPIES TO		MATL SPEC		REVISION		CHK		APD		
1	9	18	SEE NOTES	A	05/10/12	504880ERA-RELEASED FYUE				
2	10	19	FINISH N/A							
3	12	20								
4	13	21		DRW	DATE	05/02/12	SCALE	1:1		
5	14	23		CHK	DATE		SUPER DR			
6	15	33		APPD	DATE	FINISH GOOD WT				
7	16	43								
8	17	53								
TOLERANCES UNLESS OTHERWISE SPECIFIED (REF. ISO 2768-fH)		GRAMS/PIECE		TITLE		ATO FUSE HOLDER (SMART GLOW)		REVISION		
DIMENSION		UP TO		OVER		UP TO		OVER		
0.5 - 3		3 - 6		6 - 30		30 - 120		120 - 400		
TOLERANCE		±0.05		±0.1		±0.15		±0.2		
3RD ANGLE PROJECTION		DESIGNATION		LITTELFUSE		DES PLAINES, ILLINOIS 60016		REV. NO.		
								A		
								OL-0FHA0001HXGLO		