



TERM	COLOR	RECOMMENDED WIRING PER SAE J560
1	WHITE	GROUND
2	BLACK	CLEARANCE, SIDE MARKER, AND ID LAMPS
3	YELLOW	LEFT TURN AND HAZARD LAMPS
4	RED	STOP LAMPS AND ANTI-LOCK DEVICES
5	GREEN	RIGHT TURN AND HAZARD LAMPS
6	BROWN	TAIL, REAR CLEARANCE, MARKER, & LICENSE PLATE LAMPS
7	BLUE	AUXILIARY CIRCUIT (CENTER)

- NOTES:
- SIX (6) CIRCUIT TERMINALS #2 THRU #7 ACCEPT #10 GA WIRE. #1 GROUND ACCEPTS #8 GA WIRE.
 - MALE TERMINALS, SOLID PIN TYPE.
 - MEETS SAE J560 STANDARD FOR INTERCHANGEABILITY.
 - ELECTRICAL RATING:
40 AMPS CONTINUOUS DUTY AT 6-28 VOLTS D.C.
 - RECOMMENDED TERMINAL SCREW TORQUE IS 2.5-6.5 IN.LBS. (0.28-0.73 Nm).
 - RECOMMENDED MOUNTING HOLE: 2.00 DIA.
 - MATERIALS:
SHELL & COVER - GLASS FILLED NYLON (BLACK)
TERMINALS - BRASS
SPRING - STAINLESS STEEL
ALL OTHER HARDWARE - PLATED STEEL

DESIGNED BY	DRAWN BY	CHECKED BY	APPROVED BY	SCALE	PL. DEC.	PL. DEC.	ANGLES	DATE
ATG	ATG	ATG	ATG	1:1	2	3	+/-1 DEGREE	07-28-04
THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM THE JOSEPH POLLAK CORPORATION.				REVISIONS-AUTHORIZED-CHANGED-DATE ECN 14528 K REVISED AND REDRAWN LIZ 040491 17352 L MULTIPLE CHANGES, SEE ECO CS 102894 18351 M WAS PLATED BRASS (SOLID) BG BW 021797 A2266 N REDRAWN IN AUTOCAD 52 ATG 080904	MATERIAL FINISH		TITLE SOCKET, CONNECTOR 7 CONTACT - 2 HOLE MOUNT NO. 11-723 REV N	