

FT-9MM15M

Flame retardant polyester wiring harness tape test report

| adhesive tape serial number | substrate | | | Specification | | General Features | | | | | | | Scope of use |
|--------------------------------|--------------------|-------|----------------------|-----------------|-----------------|---------------------------------------|---------------------------------|---------------------|--|---------------------------------|---|---------------------|---|
| | Material | color | glue | long | Width | substrate With glue thick Spend | Tensile strength (N/cm) | Elongation (%) | Steel plate peeling force (N/cm) | Operating temperature - ℃ | Low speed unwinding force (N/cm) | Wear resistance: | This tape is primarily used for automotive wiring harnesses. It's easy to tear, waterproof, and age-resistant. It's also flame-retardant and fire-resistant. Using it for wrapping and positioning in cars can reduce vibration and noise. |
| FT-9MM15M | Polyester cloth | black | hot melt adhesive | Optional 15m | Optional 9mm | 0.16-0.18 | 180 | 15 | 2.5 | -40—105 | 2-5 | 3 00 times | |

illustrate :

The above data is obtained by our company through reliable experiments . These data may vary in different usage environments . Therefore , the above data is for reference only and does not constitute any guarantee or liability . Purchasers must independently determine the suitability of this product for their specific purpose .

